

Eka Facts

Eka HP F35

Food Grade Hydrogen Peroxide solution

General

Eka HP hydrogen peroxide solutions are clear, colorless and water-like in appearance; they can be mixed with water in any proportion. At high concentration, it has a slightly pungent or acidic odor.

Food Grade (denoted by the F in the product name) Hydrogen Peroxide is specially formulated with a low tin content stabilizer system for enhanced stability under long-term bulk storage conditions.

Applications

Eka HP F is a high purity, food grade hydrogen peroxide, suitable for use in the aseptic packaging industry.

This hydrogen peroxide grade is suitable for food industry applications where the requirements of the FDA Food Chemical Codex standard are required.

The Food Industry utilizes hydrogen peroxide for bacterial control in cheese and starch manufacture in addition to water and food disinfection.

Contact your Nouryon representative to ensure that you obtain the correct product for your particular application.

Typical properties

H ₂ O ₂ content	35 - 36 wt.%
pH	<3
Acidity (as H ₂ SO ₄)	<0.03 %
Lead	<4 ppm
Tin	<10 ppm
Iron	<0.5 ppm
Phosphate	<0.005 %
Residue on evaporation	<0.006 %

Other characteristics

Active oxygen	16.5 wt.%
Specific gravity @ 20°C (68°F)	1132 kg/m ³
Freezing point	-33°C (-27°F)
Boiling point	108°C (226°F)
Viscosity (approx.)	
@ 0°C (32°F)	1.81 cP
@ 20°C (68°F)	1.10 cP
Molecular weight	34.02
CAS Number	7722-84-1

Safety

Please refer to the current SDS (Safety Data Sheet) for preventive protection and first aid response.

Hydrogen peroxide is a very reactive oxidizing chemical and must be handled carefully. Solutions should be stored in their original containers until ready for use, and any material removed from its original container must not be returned to it. The pure material, as well as its aqueous solutions, is nonflammable.

Equipment used to handle hydrogen peroxide must be made of compatible materials such as glass, stainless steel, aluminum or HDPE.

Bohus
Jundiaí
Marietta
Shanghai

+46 31 58 7000
+55 11 4589 4800
+1 770 578 0858
+86 2 12220 5736

bleaching_experts@nouryon.com



Hydrogen peroxide must never be placed in a closed, unvented container or pipe.

Additional information on the handling of Eka HP is available in the Hydrogen Peroxide Product Information Manual that can be obtained from your Nouryon representative.

Mandatory protective equipment

Because hydrogen peroxide should never come in contact with organic materials like cloth and leather, it's imperative that workers handling the chemical always wear the appropriate protective clothing. Appropriate personal protective equipment includes all of the following:

- A protective suit (preferred anti flammable treated) made of vinyl, neoprene, or PVC.
- A pair of vinyl or neoprene boots.
- Protective goggles that fit snugly over the eyes.
- Vinyl or neoprene gloves.
- A hard-hat with a full-face shield.

Shipping

Please refer to the current SDS for the latest transportation regulations for hydrogen peroxide.

Eka HP is classified as hazardous goods and consequently transportation and packaging design must therefore adhere to all applicable transportation regulations.

Bulk shipments of hydrogen peroxide are available in tank trucks or rail car quantities. Transportation may take place by road, railway or sea.

Proper Shipping Name	Hydrogen Peroxide
UN number	2014
Transportation Hazard Class	5.1
Packaging group	II

Quality

Production at all Nouryon sites is in accordance with certified management systems. To receive a copy of the current certificate(s) please contact your Nouryon representative.

Customer Service

Nouryon representatives will be pleased to discuss in detail the safe handling, application and benefits of Eka HP.

To arrange your personal interview, please contact your Nouryon account representative, email bleaching_experts@nouryon.com or call one of the numbers below.

Bohus: +46 31 58 70 00

Marietta: +1 770 578 0858

Jundiaí: +55 11 4589 4800

Shanghai: +86 2 12220 5736

Disclaimer

Information herein is given in good faith and is accurate to the best of our knowledge. Information and suggestions are made without warranty or guarantee of results. Before using, user should determine the suitability of the product for its intended use and user assumes the risk and liability in connection therewith. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. We do not suggest violation of any existing patents or give permission to practice any patented invention without a license.

Rev. July 15, 2019